



# LEICA D-LUX 3

Creative freedom for unforgettable images

## Product Information



**Creative freedom for unforgettable images** With the LEICA D-LUX 3 every picture tells a story : the unique manual setting options offer you freedom to create images that express your own style. Use the high- quality Leica lens to take stunning shots from wide angle to the telephoto range. With O.I.S.optical image stabilization technology and processing at lightning speed, the LEICA D-LUX 3 is setting new standards in its class. Choose between 3 picture formats, achieve first-class image quality thanks to the camera's sensor with a resolution of 10 million pixels and assess your shots on the wide-screen display. Small yet elegant, the LEICA D-LUX 3 is always ready to make your personal view of the world into reality.

\_\_\_ The high-aperture **LEICA DC VARIO-ELMARIT 6.3-25.2 mm f/2.8-4.9 ASPH.** guarantees pictures in Leica quality from 28 mm wide angle to telephoto range. In conjunction with the fast **image signal processor** the D-Lux 3 can achieve such high picture quality thanks to low visual noise and fast processing.

\_\_\_ **The image stabilizer (O.I.S.)** always delivers sharply focused images even with quick snapshots, at twilight or in the zoom range.

\_\_\_ **Manual setting options** give you full freedom when creating your own pictures. But **motif programs and automatic functions** for every application also provide you with optimum picture results quickly and easily. Alone **16 scene modes** are selectable.

\_\_\_ **The 16:9 picture format with full resolution of over 10 MP** results in stunning shots and provides for reproduction on HDTV equipment. The 4:3 und 3:2 formats are selectable.

\_\_\_ The brilliant **2.8" display** also has the aspect ratio 16:9 for frame-filling presentation of acquired data.

\_\_\_ This camera is the latest classic from Leica.  
**Clean minimalist design.**

## Technical Data

Camera	LEICA D-LUX 3
<b>Image type/format</b>	1:1.65" CCD sensor with 10.4 million total pixels and 10 million effective pixels (with an aspect ratio 16:9).
<b>Resolution</b>	In <b>16:9 format</b> a choice between 4224 x 2376 pixels, 3840 x 2160 pixels, 3072 x 1728 pixels or 1920 x 1080 pixels (corresponds to HDTV standard), in <b>Leica 3:2 format</b> a choice between 3568 x 2376 pixels, 3248 x 2160 pixels, 2560 x 1712 pixels or 2048 x 1360 pixels, in <b>4:3 format</b> a choice between 3168 x 2376 pixels, 2880 x 2160 pixels, 2304 x 1728 pixels, 2048 x 1536 pixels, 1600 x 1200 pixels or 1280 x 960 pixels.
<b>Data recording</b>	<b>File formats</b> Still : RAW, JPEG (Fine/Standard), Movie : QuickTime Motion JPEG.
<b>Storage media</b>	SD memory card and multimedia card (64 MB SD card included in scope of supply).
<b>Film speed setting</b>	Choice between automatic or manual ISO 80, ISO 100, ISO 200, ISO 400, ISO 800 or ISO 1600.
<b>Lens</b>	LEICA DC VARIO-ELMARIT 6.3–25.2 mm f/2.8–4.9 ASPH. (equivalent to 28 to 112 millimeters for 35 mm format), 4x optical zoom, focal length adjustment via zoom rocker.
<b>Aperture</b>	F 2.8–F 8.0 (WW) F 4.9–F 8.0 (tele)
<b>Optical image stabilizer</b>	Two operating modes : either only for picture-taking or for both monitor and picturetaking.
<b>Distance adjustment range</b>	Choice between normal: 0.5 m (1.6 feet) (with WW)/1.2 m (3.9 feet) (with tele) to infinity, or macro: 0.05 m (0.2 feet) (with WW)/0.3 m (1 feet) (with tele) to infinity.
<b>Exposure</b>	<b>Metering</b> Choice between multiple field measurement, emphasis on middle integral measurement, spot measurement, setting can be saved. <b>Exposure modes</b> Choice between program automatic, aperture automatic, time automatic and manual setting. <b>Exposure compensation</b> ±2 EV in stages, settings from 1/3 EV.
<b>Flash</b>	<b>Flash modes</b> Choice between automatic ON with or without preflash (red-eye reduction), manual ON (fill-in flash) with or without preflash, SLOW sync for longer shutter speeds (with preflash), flash OFF. <b>Range wide</b> (sensitivity to Auto) : 0.6–4.1 m (2-13.5 feet) (with WW), 0.3–2.3 m (1-7.5 feet) (with tele). <b>Flash output adjustment</b> ±2 EV in stages, settings from 1/3 EV.
<b>Scene programs</b>	Portraits, sport, night scenes, night portraits, fireworks, parties, snow, self-portraits, food, high- sensitivity mode, Baby 1, Baby 2, soft skin, candlelight, starry skies, landscapes, print.
<b>Monitor</b>	2.8" TFT color display in 16:9 format with 207,000 pixels.
<b>Dimensions (W x H x D)</b>	105.7 x 58.3 x 25.6 mm (4.16 x 2.3 x 1.0 inch)
<b>Weight</b>	185 g/220 g (6.5/7.8 oz) (without/with battery, memory card and lens cap)
<b>Accessories</b>	
<b>Cordura Case</b>	Black <b>Order No. 18650</b> , Blue <b>Order No. 18668</b>
<b>Leather Case</b>	Cognac-brown <b>Order No. 18669</b>
<b>Direct mains connector</b>	ACA-DC4 with power cord
<b>Lithium-Ion-Battery</b>	(as spare) LEICA BP-DC4
<b>Tabletop tripod</b>	<b>Order No. 14100</b>
<b>Ball-and-socket head</b>	For short-range stand <b>Order No. 14110</b>
<b>Mini-tripod</b>	<b>Order No. 14320</b>
<b>Digital Adapter</b>	Digitaladapter 2 for LEICA TELEVID <b>Order No.42 303</b>